




PRINTED COPIES OF THIS DOCUMENT ARE FOR "REFERENCE" ONLY. CURRENT REVISIONS ARE AVAILABLE ONLINE.



DIA. DASH NO.	A ±.004	B REF	C	D +.003 -.001	P MIN	Z MIN	BK MIN	HOLE LIMITS	
								MIN	MAX
-4	.225	.035	.002-.006	.140	.010	.87	.390	.143	.146
-5	.286	.047	.002-.006	.173	.015	.94	.395	.176	.180
-6	.353	.063	.002-.006	.201	.015	.94	.410	.205	.209
-8	.476	.086	.002-.016	.267	.015	.96	.490	.271	.275

SEE SHEET 2 FOR LENGTH DIMENSIONS, MATERIALS AND FINISHES

SEE SHEET 3 FOR NOTES AND PART NUMBER EXAMPLE

NOTICE: ALL DIMENSIONS ARE IN INCHES AND APPLY AFTER FINISH AND BEFORE LUBRICATION UNLESS OTHERWISE SPECIFIED.

WARNING: FASTENERS MAY NOT PERFORM PROPERLY IF ALTERED FROM THE MANUFACTURER'S AS-SHIPED CONDITION OR INSTALLED IN CONDITIONS OTHER THAN SPECIFIED HEREIN.

PROCUREMENT SPECIFICATION: PS-CMR-3000 NAS 523 CODE: SEE SHEET 2	CHERRYMAX ® RIVET 100° FLUSH HEAD LOCKED SPINDLE (OVERSIZE)		SHEET 1 OF 3		PART NUMBER CR3242
			ISSUE	06-24-92	
			REV.	AG 02-15-18	



GRIP DASH NO.	GRIP LIMITS		-4 DIA		-5 DIA		-6 DIA		-8 DIA	
	MIN	MAX	L + .000 - .030	K MAX	L + .000 - .030	K MAX	L + .000 - .030	K MAX	L + .000 - .030	K MAX
-01	.045	.062	.200	.45	-	-	-	-	-	-
-02	(4)	.125	.238	.45	.266	.47	.265	.48	-	-
-03	.126	.187	.301	.52	.309	.53	.328	.55	.375	.64
-04	.188	.250	.363	.58	.371	.60	.390	.62	.437	.70
-05	.251	.312	.426	.65	.434	.66	.453	.68	.500	.77
-06	.313	.375	.488	.71	.496	.72	.515	.74	.562	.83
-07	.376	.437	.551	.78	.559	.79	.578	.82	.625	.89
-08	.438	.500	.613	.84	.621	.85	.640	.89	.687	.95
-09	.501	.562	.676	.90	.684	.91	.703	.95	.750	1.02
-10	.563	.625	-	-	.746	.98	.765	1.01	.812	1.08
-11	.626	.687	-	-	.809	1.04	.828	1.07	.875	1.14
-12	.688	.750	-	-	.871	1.10	.890	1.14	.937	1.20
-13	.751	.812	-	-	-	-	-	-	1.000	1.27
-14	.813	.875	-	-	-	-	-	-	1.062	1.60

FINISH CODE	NAS 523 CODE	MATERIAL (5)			FINISH		
		SLEEVE	STEM	LOCK COLLAR	SLEEVE	STEM	LOCK COLLAR
-	ARD	5056 ALUM. PER QQ-A-430	8740 STEEL PER AMS 6322	A-286 CRES PER AMS 5731 & AMS 5737	CHEM. FILM PLAIN COLOR PER MIL-C-5541	CAD. PLATE PER QQ-P-416 TYPE II, CL.2	PASSIVATE PER AMS 2700
A	-	5056 ALUM. PER QQ-A-430	8740 STEEL PER AMS 6322	A-286 CRES PER AMS 5731 & AMS5737	CHEM. FILM PLAIN COLOR PER MIL-C-5541	CAD. PLATE PER QQ-P-416 TYPE II, CL.2	PASSIVATE PER AMS 2700
(10) PR	-	5056 ALUM. PER QQ-A-430	8740 STEEL PER AMS 6322	A-286 CRES PER AMS 5731 & AMS5737	CHEM. FILM PLAIN COLOR PER MIL-C-5541	CAD. PLATE PER QQ-P-416 TYPE II, CL.2	PASSIVATE PER AMS 2700
(8) T	-	5056 ALUM. PER QQ-A-430	8740 STEEL PER AMS 6322	A-286 CRES PER AMS 5731 & AMS5737	CHEM. FILM PLAIN COLOR PER MIL-C-5541	CAD. PLATE PER QQ-P-416 TYPE II, CL.2	PASSIVATE PER AMS 2700


SHEET 2 OF 3		PART NUMBER
ISSUE	06-24-92	
REV.	AG	02-15-18
CR3242		



NOTES:

- ① HEAD MARKINGS AND LOCK COLLAR VISIBLE AFTER INSTALLATION.
- ② SILVER COLORED DRIVING ANVIL IDENTIFIES OVERSIZE DIAMETER RIVETS.
- ③ MINIMUM BLIND SIDE CLEARANCE FOR SATISFACTORY INSTALLATION.
- ④ MINIMUM GRIP FOR -4 DIA. IS .063; FOR -5 IS .063; AND FOR -6 IS .073.
- ⑤ MATERIAL DESIGNATION REFERS TO CHEMICAL COMPOSITION ONLY.
- 6. SHEET THICKNESS FOR MACHINE COUNTERSUNK HOLES SHALL NOT BE LESS THAN "B" +.010.
- ⑦ SINGLE DIGIT HEAD MARKING IS PERMISSIBLE, AT MANUFACTURER'S OPTION, FOR GRIP DASH NUMBERS LESS THAN 10.
- ⑧ "T" CODE - PARTS ARE MANUFACTURED BARE; IF LUBE IS REQUIRED, USE TRANSLUBE 20204 ONLY. TRANSLUBE ("T" CODE) WILL BE UNAVAILABLE FOR PROCDUREMENT AS OF 01-01-92.
- ⑨ A DASH MAY BE MARKED UNDER OR TO THE RIGHT SIDE OF THE GRIP IDENTIFICATION AT MANUFACTURER'S OPTION.
- ⑩ "PR" CODE – PARTS ARE MANUFACTURED BARE; IF LUBE IS REQUIRED, USE PAR 90 ONLY.

EXAMPLE OF CHERRY PART NUMBER:



SHEET 3 OF 3		PART NUMBER
ISSUE	06-24-92	
REV.	AG	02-15-18
CR3242		

STANDARDS PAGE REVISION LOG

REV LTR	DATE	DCR NUMBER	REVISION DESCRIPTION	COMP. BY
AG	02-1518	18-0186	<ul style="list-style-type: none">• ADD MISSING \pm SYMBOL TO DIMENSION "A" BEFORE .004.	AA